

■アウトリガ最大（4.5m）張出 [全周]

ブーム長さ 作業半径 (m)	5.5m ブーム	9.1m ブーム	12.7 mブーム	16.3 mブーム	19.9 mブーム	23.5 mブーム
1.5	4.90	4.90	4.90			
2.0	4.90	4.90	4.90	4.90		
2.5	4.90	4.90	4.90	4.90		
3.0	4.90	4.90	4.90	4.00	4.00	
3.0	4.90	4.90	4.90	4.00	4.00	
3.5	4.90	4.90	4.90	4.00	4.00	2.30
4.0	4.90	4.90	4.90	4.00	4.00	2.30
4.5		4.90	4.55	4.00	3.70	2.30
5.0		4.40	4.10	3.70	3.40	2.30
5.5		3.95	3.70	3.40	3.10	2.30
6.0		3.55	3.35	3.15	2.85	2.30
6.5		3.15	3.05	2.90	2.60	2.15
7.0		2.80	2.80	2.65	2.40	2.00
8.0		2.50	2.30	2.25	2.05	1.75
9.0			1.90	1.95	1.80	1.55
10.0			1.55	1.70	1.60	1.40
11.0			1.20	1.45	1.40	1.25
12.0				1.20	1.25	1.15
13.0				0.95	1.05	1.05
14.0				0.80	0.90	0.95
15.0				0.70	0.75	0.85
16.0					0.65	0.70
17.0					0.55	0.60
18.0					0.45	0.50
19.0						0.42
20.0						0.35
21.0						0.30
22.0						0.25
危険角度	---	---	---	---	---	---

■外形寸法図 (単位: mm)

