

■アウトリガ最大（6.3m）張出 [全周]

■外形寸法図（単位：mm）

| ブーム長さ 作業半径 (m) | 9.5mブーム | 16.5mブーム | 23.5mブーム | 30.5mブーム |
|----------------------|---------|----------|----------|----------|
| 2.5 | 25.00 | 18.00 | | |
| 3.0 | 25.00 | 18.00 | 12.50 | |
| 3.5 | 25.00 | 18.00 | 12.50 | |
| 4.0 | 23.00 | 18.00 | 12.50 | 7.00 |
| 4.5 | 21.20 | 18.00 | 12.50 | 7.00 |
| 5.0 | 19.40 | 16.70 | 12.50 | 7.00 |
| 5.5 | 17.80 | 15.60 | 11.85 | 7.00 |
| 6.0 | 16.30 | 14.60 | 11.20 | 7.00 |
| 6.5 | 15.10 | 13.80 | 10.60 | 7.00 |
| 7.0 | | 13.00 | 10.10 | 7.00 |
| 7.5 | | 12.20 | 9.60 | 6.40 |
| 8.0 | | 10.90 | 9.10 | 7.00 |
| 9.0 | | 8.65 | 8.20 | 6.40 |
| 10.0 | | 7.05 | 7.40 | 5.90 |
| 11.0 | | 5.85 | 6.50 | 5.35 |
| 12.0 | | 4.95 | 5.55 | 4.90 |
| 13.0 | | 4.20 | 4.75 | 4.50 |
| 13.5 | | 3.90 | 4.40 | 4.30 |
| 14.0 | | | 4.10 | 4.15 |
| 15.0 | | | 3.60 | 3.85 |
| 15.5 | | | 3.40 | 3.70 |
| 16.0 | | | 3.15 | 3.45 |
| 17.0 | | | 2.80 | 3.05 |
| 18.0 | | | 2.45 | 2.70 |
| 19.0 | | | 2.15 | 2.45 |
| 20.0 | | | 1.90 | 2.20 |
| 20.5 | | | 1.80 | 2.05 |
| 21.0 | | | | 1.95 |
| 22.0 | | | | 1.75 |
| 24.0 | | | | 1.40 |
| 26.0 | | | | 1.15 |
| 27.5 | | | | 0.95 |
| 危険角度 | --- | --- | --- | --- |

